

Classroom Speaker Options

Single Speaker Solution

Lightspeed's flat panel speakers produce a very wide dispersion of sound, resulting in excellent distribution throughout the entire classroom from a single speaker. Installation is very simple and speech intelligibility is superb.



MCQ Multimedia Ceiling Speaker **NEW**

Two-way hybrid speaker system with NXT™ distributed mode panel and low frequency cone driver delivers clear audio, excellent sound distribution and high speech intelligibility.

Specifications

- Description: NXT* Distributed Mode Panel*
- Panel Size: 16.25" x 8.25"
- Driver Size: 6.5" driver
- Frequency Response: 80 Hz - 20 kHz ± 10dB
- Impedance: 4 Ohms
- Power Handling: 15 W RMS
- Dimensions: 24" x 24" x 3"
- Weight: 14 lbs



CNXQ Flat Panel Ceiling Speaker

Designed for classrooms with suspended ceilings between 9 and 12 feet, these low-profile speakers provide excellent speech intelligibility and distribute sound evenly throughout the classroom.

Specifications

- Description: NXT* Distributed Mode Panel*
- Panel Size: 22.25" x 22.25"
- Frequency Response: 60 Hz - 20 kHz
- Impedance: 4 Ohms
- Power Handling: 15 W
- Dimensions: 24" x 24" x 1.5"
- Weight: 4.5 lbs



NXQ Flat Panel Wall Speaker

Built for classrooms where ceiling speakers are not practical, the NXQ is wall-mounted and provides optimum speech intelligibility. This speaker is ideally suited for classrooms with ceilings higher than 9 feet.

Specifications

- Description: NXT* Distributed Mode Panel*
- Panel Size: 16.25" x 8.25"
- Frequency Response: 100 Hz - 20 kHz
- Impedance: 8 Ohms
- Overall Dimensions: 18.25" x 10.25" x 1.5"
- Weight: 2.2 lbs
- Mounted on standard picture hanger

* NXT™ is a trademark of New Transducers Limited

Traditional Speaker Solutions

For larger or multimedia classroom applications, we offer a line of traditional speakers, which places multiple speakers around the classroom. These speaker solutions cover classrooms up to 1600 square feet and will deliver a full range of sound.



DRQ Ceiling Speaker

Low-profile speakers designed for rooms with suspended ceilings and deliver high quality, full-range sound. Four speakers will distribute sound evenly throughout classrooms with room heights between 9 and 12 feet.

Specifications

- Description: Two-way speaker system
- Driver Size: 6.5" driver; 1" horn
- Frequency Response: 40 Hz - 20 kHz
- Impedance: 8 Ohms
- Power Handling: 30 W
- Dimensions: 9.5" diameter; 5.5" deep
- Weight: 5.9 lbs



WMQ Wall Speaker

Four WMQ speakers provide high quality distributed sound for classrooms with solid ceilings as low as 8 feet.

Specifications

- Description: Mini 2-way / Capacitive Crossover
- Driver Size: 3" Acoustic Suspension Driver
- Frequency Response: 110 Hz - 20 kHz
- Impedance: 8 Ohms
- Power Handling: 30 W
- Dimensions: 6.35" x 3.8" x 4.13"
- Weight: 1.5 lbs

Contact us:

LIGHTSPEED TECHNOLOGIES
11509 SW HERMAN ROAD / TUALATIN, OREGON 97062
TOLL FREE: 1.800.732.8999 / PHONE: 503.684.5538 / FAX: 503.684.3197
WWW.LIGHTSPEED-TEK.COM